



Spacer 6-fold



Product description:

The 6-fold spacer is made of polyolefin, in black (RAL 9005).

This spacer is used to ensure exact spacing during the installation of Kabuflex conduit systems.



Special features

For the installation of Kabuflex® S, spacers should be spaced approx. 1.5 m apart. For the installation of Kabuflex® R or Kabuflex® R plus, the spacing must be reduced.

Cat. No.:	Type	Conten	PU	Weight PU/kg	Overall width mm	Overall height mm	Depth mm
199 46 075	75	1	PCS	0,063	317,0	130,0	19,0
199 46 110	110	1	PCS	0,215	421,0	208,0	30,0
199 46 120*	120	1	PCS	0,274	461,0	218,0	32,0
199 46 160	160	1	PCS	0,350	661,0	311,0	33,0
199 46 200	200	1	PCS	0,980	846,0	347,0	25,0

*also suitable for DN 125

All dimensions without tolerances are for information only.



Spacer 6-fold

Material properties

Zero halogen	EN 50642	•
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	
UV-resistant	DIN EN ISO 4892	
Highspeed		

Fields of application

on plaster	machines	
under plaster	hot asphalt	
on wood	under screed	
underground installation	• prefabricated construction	
in concrete	outdoor	

Chemical properties

Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, beer, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
Limitedly resistant to	gasoline, benzene, nitric acid
Not resistant to	gaseous dry chlorine, terpentine

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123