



ASG-E

**Product description:**

ASG-E is an aluminium clamp, with pan-head screw M5x12 Zinc-Nickel coated.

This clamp is used for Alu Gewinde-ES aluminium conduits and for Alu Steck-ES.



VDE 0605
DIN EN 61386-21



Cat. No.:	Type	Content	PU	Weight PU/kg	Overall width mm	Overall height mm	Overall length mm	Borehole Ø mm	Recommended Distance cm
209 75 016	16	50	PCS	0,600	16,0	28,0	43,0	6,2x10	70
209 75 020	20	50	PCS	0,700	16,0	32,0	50,0	6,2x10	70
209 75 025	25	50	PCS	0,850	16,0	37,0	58,0	6,2x10	70
209 75 032	32	25	PCS	0,575	16,0	44,0	70,0	6,2x10	70
209 75 040	40	25	PCS	0,600	16,0	52,0	80,0	6,2x14	70
209 75 050	50	25	PCS	0,775	16,0	62,0	86,0	6,2x14	70
209 75 063	63	20	PCS	0,620	16,0	75,0	96,0	6,2x14	70

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-21:2011 Conduit systems for cable management - Part 21: Particular requirements - Rigid conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

All dimensions without tolerances are for information only.



ASG-E

Material properties		Fields of application	
Zero halogen	DIN VDE V 0604-2-100	on plaster	• machines
Low smoke	DIN EN 61034-2	under plaster	• hot asphalt
Non-flame propagating	DIN EN 61386-1	• on wood	• under screed
UV-resistant	DIN 53387	underground installation	prefabricated construction
Highspeed		in concrete	outdoor

Chemical properties	
Resistant to	gasoline, benzene, diesel fuel, photographic developer, methanol, propane
Limitedly resistant to	gaseous dry chlorine
Not resistant to	acid emissions, nitric acid, hydrochloric acid, sulfuric acid

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-21 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

