



## E-Ku-ET-UV



### Product description:

E-Ku-ET-UV is a divisible plastic push-fit end cap made of polyolefin, in black (RAL 9005), non-flame propagating, zero halogen.

This end cap is used as edge protection for all straight length and metal conduits.



### Special features

UV-resistant for up to 10 years.

Cat. No.:	Type	Content	PU	Weight PU/kg	Overall width mm	Overall height mm	Overall length mm
259 98 020	20	100	PCS	0,210	22,0	15,0	51,5
259 98 025	25	100	PCS	0,310	27,0	17,5	62,0
259 98 032	32	50	PCS	0,225	32,0	21,0	76,0
259 98 040	40	50	PCS	0,295	34,0	25,0	92,0
259 98 050	50	25	PCS	0,248	44,0	30,0	112,0

### Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-21:2011 Conduit systems for cable management - Part 21: Particular requirements - Rigid conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

All dimensions without tolerances are for information only.



## E-Ku-ET-UV

Material properties		Fields of application	
<b>Zero halogen</b>	<b>DIN VDE V 0604-2-100</b>	• <b>on plaster</b>	• <b>machines</b>
Low smoke	DIN EN 61034-2	• <b>under plaster</b>	• <b>hot asphalt</b>
<b>Non-flame propagating</b>	<b>DIN EN 61386-1</b>	• <b>on wood</b>	• <b>under screed</b>
<b>UV-resistant</b>	<b>DIN 53387</b>	• <b>underground installation</b>	• <b>prefabricated construction</b>
Highspeed		• <b>in concrete</b>	• <b>outdoor</b>

Chemical properties	
<b>Resistant to</b>	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, beer, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
<b>Limitedly resistant to</b>	benzene, gaseous dry chlorine, nitric acid, terpentine
<b>Not resistant to</b>	-

## Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-21 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

## Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

