



Furowell end cap

Product description:



PE-HD end cap, zero halogen, DN 250 available in yellow, and DN 300 and DN 350 available in black.

This end cap is used as temporary construction phase cover for Furowell. Cannot be walked on or driven on.



Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU	Weight PU/kg
295 70 250	250	253	293	1	PCS	0,094
295 70 300	300	300	346	1	PCS	0,530
295 70 350	350	345	400	1	PCS	0,375

All dimensions without tolerances are for information only.



Furowell end cap

Material properties

Zero halogen	EN 50642	•
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	
UV-resistant	DIN 53387	
Highspeed		

Fields of application

on plaster		machines	
under plaster		hot asphalt	
on wood		under screed	
underground installation	•	prefabricated construction	
in concrete		outdoor	

Chemical properties

Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, beer, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
Limitedly resistant to	benzene, gaseous dry chlorine, nitric acid, terpentine
Not resistant to	-

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123