



FA 150 DE-KD

Product description:

The FA 150 DE-KD sealing insert is a cable and conduit lead-through for use in the FA 150 VBF front flange.

The advantages are the system's interaction with the FA 150 VBF front flange and the segmented inserts for the gas-tight and pressure water-tight feed-through of power cables and electrical conduits from pressure resistance 3.



Cat. No.:	Outside Ø mm	Content	PU	Weight PU/kg	Thread	for conduits Ø mm	For cable Ø mm	sealing width mm
197 22 360	159	1	PCS	1,620	M6	3x 7-54	3x 7-54	30
197 22 640	159	1	PCS	1,700	M8	6x 7-36	6x 7-36	30

All dimensions without tolerances are for information only.

FA 150 DE-KD

Properties

Chemicals resistant to	water, dirty water, nitrogen, radon, methane, ozone, many alcohols, alkalis, acids, coolants and solvents
Mechanical properties	abrasion resistance, wear resistance, impact resistance, heat resistance
Technical characteristics	compressive flanges: stainless steel V2A; connectors: stainless steel V2A; elastomer: PUR, EPDM

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

