



## FA 150 VBF

### Product description:



FA 150 VBF is a sealing flange for dowelling over core drillings and openings up to 150 mm. The advantage is the system connection of FA 150 sealing inserts and system covers for the gas-tight and water pressure-tight building lead-through of Kabuflex R plus conduits, power cables, and electrical conduits from pressure resistance 3.

The front flange can be used in structures made of waterproof concrete, structures with a surface sealing according to DIN 18533 ("black tank"), and for screwing onto housings.



Cat. No.:	Inside Ø mm	Content	PU	Weight PU/kg	Overall width mm	Overall height mm	Overall length mm	Hole spacing mm	Core drilling mm	sealing width mm
197 01 009	161	1	PCS	2,020	232,0	67,0	232,0	183,0	0-150	10

All dimensions without tolerances are for information only.



## FA 150 VBF

General information	
<b>Technical notes</b>	aluminum front flange, solid rubber core (EPDM) sealing plate (10 mm)
<b>Application</b>	W1-E and W2.1-E according DIN18533 stress class 1 and 2 according DAfStb-policy
<b>Delivery includes</b>	1x front flange, 1x sealing plate, 4x screws (width 12, 7x90), 4x screw washers, 4x wall plugs M10

**Hotline**  
 Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time. **Information can be obtained from our technical consultants at +49 9525 88-8123**

