



## FHA red with mating pins



### Product description:

FHA is a PVC-U cable protector with mating pins and available in red.

This cable protector is used for the safe underground installation of high-voltage and low-voltage cables, and telecommunications, signal and control lines. Advantages are that underground wires and cables are reliably detected and the tight-fitting and secure connection.

Temperature resistance range: -5° C to +60° C



Cat. No.:	Type	Content	PU	Weight PU/kg	Pallet content m	Overall width mm	Overall length mm
181 20 110	110	1	m	0,150	1.500	110,0	500,0
181 20 120	120	1	m	0,160	1.500	120,0	500,0
181 20 160	160	1	m	0,200	1.500	162,0	500,0
181 20 180	180	1	m	0,240	1.000	182,0	500,0
181 20 200	200	1	m	0,280	1.000	202,0	500,0
181 40 110	110	1	m	0,300	1.500	110,0	1000,0
181 40 120	120	1	m	0,320	1.500	120,0	1000,0
181 40 160	160	1	m	0,400	1.500	162,0	1000,0
181 40 180	180	1	m	0,480	1.000	182,0	1000,0
181 40 200	200	1	m	0,560	1.000	202,0	1000,0

All dimensions without tolerances are for information only.



## FHA red with mating pins

## Fields of application

on plaster		machines	
under plaster		hot asphalt	
on wood		under screed	
<b>underground installation</b>	•	prefabricated construction	
in concrete		outdoor	

## Chemical properties

<b>Resistant to</b>	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, nitric acid, hydrochloric acid, sulfuric acid, turpentine, detergent
<b>Limitedly resistant to</b>	gaseous dry chlorine
<b>Not resistant to</b>	benzene, beer

## Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

