



Fibre net DSM

Product description:



Fibre net DSM is a halogen-free and flame resistant coupling available in white.

This gastight and watertight coupling is used to connect FFKu-Fibre net. Temperature range: 0–50 °C.



Special features

Pressure: gastight and watertight 0.5 bar; 15 bar/30 min
Burst pressure: min. 30 bar

Cat. No.:	Type	Content	PU	Weight PU/kg	Overall length mm	Outside Ø mm with tabs	for conduits Ø mm
265 50 007	7	25	PCS	0,108	32,0	13,0	7
265 50 010	10	25	PCS	0,300	42,0	18,0	10
265 50 012	12	25	PCS	0,475	46,0	22,0	12
265 50 014	14	25	PCS	0,550	47,0	24,0	14

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in part

EN 61386-22:2011 Conduit systems for cable management - Part 22: Particular requirements - Pliable conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in part

All dimensions without tolerances are for information only.



Fibre net DSM

Material properties		
Zero halogen	EN 50642	
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	•
UV-resistant	DIN EN ISO 4892	
Highspeed		

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-22 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123