



Fibre net ES

Product description:



Fibre net ES is a halogen-free and flame resistant end plug available in white.

This end plug is used to provide gastight and watertight seals of FFKu-Fibre net.
Temperature range: 0–50 °C.



Special features

Pressure: gastight and watertight 0.5 bar; 15 bar/30 min
Burst pressure: min. 30 bar

Cat. No.:	Type	Content	PU	Weight PU/kg	Overall length mm	Outside Ø mm with tabs	for conduits Ø mm
265 70 007	7	25	PCS	0,050	17,0	13,0	7
265 70 010	10	25	PCS	0,150	22,0	18,0	10
265 70 012	12	25	PCS	0,300	25,0	21,0	12
265 70 014	14	25	PCS	0,300	25,0	23,0	14

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in part

EN 61386-22:2011 Conduit systems for cable management - Part 22: Particular requirements - Pliable conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in part

All dimensions without tolerances are for information only.



Fibre net ES

Material properties		
Zero halogen	EN 50642	
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	•
UV-resistant	DIN EN ISO 4892	
Highspeed		

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-22 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

