



Fibre net IB

Product description:



Fibre net IB is a halogen-free and flame resistant bend available in white.

This bend is used to reroute FFKu-Fibre net. Fibre net IB can be connected.



Cat. No.:	Type	Content	PU	Weight PU/kg	Overall width mm	Overall height mm	Overall length mm	for conduits Ø mm
265 60 007	7	25	PCS	0,575	75,0	125,0	110,0	7

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in part

EN 61386-22:2011 Conduit systems for cable management - Part 22: Particular requirements - Pliable conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in part

All dimensions without tolerances are for information only.



Fibre net IB

Material properties

Zero halogen	EN 50642	
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	•
UV-resistant	DIN EN ISO 4892	
Highspeed		

Fields of application

on plaster	•	machines	
under plaster	•	hot asphalt	
on wood	•	under screed	•
underground installation		prefabricated construction	•
in concrete	•	outdoor	

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-22 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

