



Fibre net KmR



Product description:

Fibre net KmR is a halogen-free and flame resistant label with pipe plug available in white.

This label with pipe plug is used to provide gastight and watertight seals and label FFKu-Fibre net. Fibre net KmR can be labelled with permanent marker in the branch section. This seals unused conduits. When using the conduit, you can break off the protective cover and move it backwards. The conduit remains labelled and can be used. Temperature range: 0–50 °C.



Special features

Pressure: gastight and watertight 0.5 bar

Cat. No.:	Type	Content	PU	Weight PU/kg	Overall length mm	Outside Ø mm with tabs	for conduits Ø mm
265 71 007	7	25	PCS	0,380	122,0	20,0	7
265 71 010	10	25	PCS	0,500	122,0	20,0	10
265 71 012	12	25	PCS	0,500	122,0	20,0	12
265 71 014	14	25	PCS	0,500	122,0	23,0	14

All dimensions without tolerances are for information only.



Fibre net KmR

Material properties		
Zero halogen	EN 50642	
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	•
UV-resistant	DIN EN ISO 4892	
Highspeed		

Risk analysis

The product has been manufactured and tested according to the harmonized standard in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

