



## FRVS-E

### Product description:



FRVS- E is a PE conduit blanking plug, in different colours, non-flame propagating, zero halogen.

This conduit blanking plug is used for covering and sealing conduits at construction sites and for plugging unused conduits.



Exemplary illustration of NW 25



### Special features

5 tags included with every package.

colour marking:

NW 16 red, NW 20 green, NW 25 violet, NW 32 blue, NW 40 yellow, NW 50 green and NW 63 violet


Cat. No.:	Type	Outside Ø mm	Content	PU	Weight PU/kg	Overall length mm
259 70 016	16	15	100	PCS	0,100	33,0
259 70 020	20	18	100	PCS	0,100	31,0
259 70 025	25	23	100	PCS	0,200	34,0
259 70 032	32	34	50	PCS	0,150	37,0
259 70 040	40	37	50	PCS	0,250	37,0
259 70 050	50	49	25	PCS	0,200	40,0
259 70 063	63	59	10	PCS	0,110	42,0

### Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-22:2011 Conduit systems for cable management - Part 22: Particular requirements - Pliable conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

All dimensions without tolerances are for information only.





## FRVS-E

Material properties		
<b>Zero halogen</b>	<b>EN 50642</b>	•
Low smoke	DIN EN 61034-2	
<b>Non-flame propagating</b>	<b>DIN EN 61386-1</b>	•
UV-resistant	DIN EN ISO 4892-1	
Highspeed		

Fields of application			
<b>on plaster</b>	•	<b>machines</b>	•
<b>under plaster</b>	•	hot asphalt	
<b>on wood</b>	•	<b>under screed</b>	•
<b>underground installation</b>	•	<b>prefabricated construction</b>	•
<b>in concrete</b>	•	outdoor	

Chemical properties	
<b>Resistant to</b>	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
<b>Limitedly resistant to</b>	benzene, gaseous dry chlorine, nitric acid, terpentine
<b>Not resistant to</b>	-

Accessories		
	Identification plate	159 71 ...

**Risk analysis**  
 The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-22 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

**Hotline**  
 Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time. **Information can be obtained from our technical consultants at +49 9525 88-8123**

