



Kabu-BV

Product description:



Kabu-BV is an end plug made of a solid rubber core (EPDM) with a soft thermoset elastomer (PUR) jacket in yellow and stainless steel compressive flanges.

This gas and water pressure-tight end plug is used for Kabuflex® conduits for building penetrations. The advantage is its soft surface which creates a reliable seal against gas and water pressure.



Special features

Thanks to its very good adhesive properties, the Kabu-BV end plug fits reliably (against pressing water and gas) in the conduit. It can be installed successfully without using special tools (torque spanner) via visual indication (yellow bead) at the compressive flange edges. When positioning, please make sure that the internal seal is in the area of the unfinished flooring or screed and/or the Kabu Seal outside seal to establish a reliable seal.

Cat. No.:	Type	Outside Ø mm	Content	PU	Weight PU/kg	sealing width mm	for conduits Kabuflex Type
199 50 063	63	50	1	PCS	0,180	30	63
199 50 075	75	61	1	PCS	0,263	30	75
199 50 110	110	92	1	PCS	0,581	30	110
199 50 160	160	135	1	PCS	1,225	30	160

All dimensions without tolerances are for information only.



Kabu-BV

Properties

Chemicals resistant to	oils, greases, many solvents, aromatic fuels (gasoline, kerosene, methane), acetone, alcohol, salt water
Mechanical properties	abrasion resistance, tear resistance, wear resistance, impact resistance, heat resistance
Technical characteristics	compressive flanges: stainless steel V2A; connectors: stainless steel V2A; elastomer: PUR / (EPDM)

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

