



## Kabu-Seal

### Product description:



Kabu-Seal is a pressure sealing ring made of a solid rubber core (EPDM) with a soft thermoset elastomer (PUR) jacket in yellow and compressive flanges made of stainless steel.

This water pressure-tight wall lead through is used for Kabuflex® conduits for building and wall lead throughs. An advantage is its soft surface which offers sealing of the cable duct and core drill hole up to 1.5 bar water pressure.



### Special features

Thanks to its very good adhesive properties, the Kabu Seal pressure sealing ring seals reliably (against pressurised water and gas) in the annular space even with very low tightening torque of the screw connection. Can be installed successfully without using special tools (torque spanner) at sight (yellow bead) at the compressive flange edges.

Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU	Weight PU/kg	Overall width mm	Core drilling mm	for conduits Ø mm
199 65 063	63	64	100	1	PCS	0,570	60,0	100	63,0
199 65 075	75	76	122,8	1	PCS	0,945	60,0	125	75,0
199 65 110	110	111	150	1	PCS	0,940	60,0	150	110,0
199 65 160	160	162	198,3	1	PCS	1,515	80,0	200	160,0

All dimensions without tolerances are for information only.



## Kabu-Seal

### Properties

<b>Chemicals resistant to</b>	oils, greases, many solvents, aromatic fuels (gasoline, kerosene, methane), acetone, alcohol, salt water
<b>Mechanical properties</b>	abrasion resistance, tear resistance, wear resistance, impact resistance, heat resistance
<b>Technical characteristics</b>	density: 1,5 bar (15m WS) ; cpmressive flanges: stainless steel V2A / 3mm; connectors: 6 kits M6 stainless steel V2A; elastomer: EPDM / PUR

### Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

**Information can be obtained from our technical consultants at +49 9525 88-8123**

