

Kabuflex 90° bend black

N450

Product description:



The Kabuflex 90 degree bend is a structured-wall PE connecting bend, in black.

This bend is used to create a small bend radius and to install Kabuflex® S straight length conduits in confined space. Special couplings connect bend and conduit sandtight (SD). The WD profile sealing ring produces a watertight joint up to 0.5 bar. An advantage is the high compressive strength.



DIN EN 61386-24
Compressive strength: Type 450
Temperature range from -5 °C to +90 °C



Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU	Weight PU/kg	Bend radius > mm	Length m
190 80 075	75	63	75	5	PCS	2,825	750	1,5
190 80 110	110	93	110	5	PCS	5,350	900	1,8
190 80 120	120	99	120	5	PCS	6,850	900	1,9
190 80 125	125	107	125	5	PCS	7,925	1.100	2,0
190 80 145	145	125	145	5	PCS	9,550	1.100	2,2
190 80 160	160	137	160	5	PCS	11,025	1.100	2,2
190 80 175	175	149	175	5	PCS	13,800	1.100	2,2

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-24:2011 Conduit systems for cable management - Part 24: Particular requirements - Conduit systems buried underground / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

Outside diameter according to DIN EN 61386-24
All dimensions without tolerances are for information only.



Kabuflex 90° bend black

N450

Material properties

Zero halogen	EN 50642	•
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	
UV-resistant	DIN 53387	
Highspeed		

Fields of application

on plaster		machines	
under plaster		hot asphalt	
on wood		under screed	
underground installation	•	prefabricated construction	
in concrete		outdoor	

Chemical properties

Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
Limitedly resistant to	benzene, gaseous dry chlorine, nitric acid, terpentine
Not resistant to	-

Accessories

Coupling	Kabuflex coupling	199 10 ...
Sealing ring	Kabuflex profile sealing ring	199 80 ...
Wall lead through	Wall collar set	199 60 ...
End cap	Kabuflex SD end cap	199 70 ...
End cap	Kabuflex WD end cap	199 71 ...
Spacer	Spacer 2-fold	199 42 ...
Spacer	Spacer 4-fold	199 44 ...
Spacer	Spacer 6-fold	199 46 ...
Spacer	Spacer 8-fold	199 48 ...
Adaptor	Reducer	199 95 ...
Pressure sealing ring	Kabu-Seal	199 65 ...

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-24 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123