



Kabuflex SD end cap



Product description:

The SD end cap is made of polyolefin, in transparent, partially in yellow.

This end cap is used to permanently or temporarily close and seal Kabuflex® conduits. An advantage is the sandtight sealing.



Cat. No.:	Type	Content	PU	Weight PU/kg
199 70 040	40	1	PCS	0,010
199 70 050	50	1	PCS	0,010
199 70 063	63	1	PCS	0,010
199 70 075	75	1	PCS	0,010
199 70 090	90	1	PCS	0,020
199 70 110	110	1	PCS	0,020
199 70 120	120	1	PCS	0,020
199 70 125	125	1	PCS	0,024
199 70 145	145	1	PCS	0,040
199 70 160	160	1	PCS	0,040
199 70 175	175	1	PCS	0,040

All dimensions without tolerances are for information only.





Kabuflex SD end cap

Material properties		
Zero halogen	EN 50642	•
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	
UV-resistant	DIN 53387	
Highspeed		

Fields of application			
on plaster		machines	
under plaster		hot asphalt	
on wood		under screed	
underground installation	•	prefabricated construction	
in concrete		outdoor	

Chemical properties	
Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, beer, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
Limitedly resistant to	benzene, gaseous dry chlorine, nitric acid, terpentine
Not resistant to	-

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

