



Kabuflex WD end cap



Product description:

The WD end cap is made of polyolefin, in black, watertight profile sealing ring included.

This end cap is used to permanently or temporarily close and seal Kabuflex® conduits. An advantage is that conduits can be retrofitted to be closed and sealed to be protected against water ingress.



Cat. No.:	Type	Content	PU	Weight PU/kg	Overall length mm
199 71 110	110	1	PCS	0,030	102,0
199 71 120	120	1	PCS	0,144	108,0
199 71 125	125	1	PCS	0,144	109,0
199 71 160	160	1	PCS	0,200	122,0
199 71 175	175	1	PCS	0,265	93,0

*profile sealing ring included.

All dimensions without tolerances are for information only.



Kabuflex WD end cap

Material properties		Fields of application	
Zero halogen	DIN VDE V 0604-2-100	• on plaster	machines
Low smoke	DIN EN 61034-2	under plaster	hot asphalt
Non-flame propagating	DIN EN 61386-1	on wood	under screed
UV-resistant	DIN 53387	underground installation	• prefabricated construction
Highspeed		in concrete	outdoor

Chemical properties	
Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, beer, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
Limitedly resistant to	benzene, gaseous dry chlorine, nitric acid, terpentine
Not resistant to	-

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

