



Kabuflex R plus 450 co2ntrol

N450

**Product description:**

Kabuflex® R plus 450 co2ntrol is a pliable and eco-balanced PE cable conduit available in black. Thanks to its composite design with optimised green inner surface, cables can be inserted quickly. The halogen-free product also features high compressive strength as well as improved stability thanks to the high-quality materials used.

This conduit is used for installations underground. The delivery includes an attached transparent coupling (sandtight) and a feed cord. The separately available profile sealing ring produces a watertight connection (WD) of up to 0.5 bar.



DIN EN 61386-24
Compressive strength: Type 450
Temperature range from -5 °C to +90 °C

**Special features**

These CO₂-reduced conduits were subjected to a systematic analysis of all input and output flows across their entire life according to DIN EN ISO 14040 and DIN EN ISO 14044. An EPD (environmental product declaration) was prepared for this and certified by the independent verification body IBU (Institut Bauen und Umwelt e.V.) according to DIN EN ISO 14025 and DIN EN 15804. Accessories are not taken into account in terms of the ecobalance. (Former product name Kabuflex R plus Typ 450)

Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU	Weight PU/kg	Bend radius > mm
192 10 040	40	31	40	50	m	7,3	350
192 10 050	50	40	50	50	m	9,6	350
192 10 063	63	52	63	50	m	13,6	350
192 10 075	75	62	75	50	m	16,6	350
192 10 090	90	75	90	50	m	21,7	350
192 10 110	110	93	110	50	m	27,2	500
192 10 125	125	106	125	25	m	18,0	600
192 10 160	160	137	160	25	m	28,9	750
192 10 200	200	173	200	25	m	40,6	750

Standardisation

EN 61386-1:2008 + A1:2019 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-24:2010 Conduit systems for cable management - Part 24: Particular requirements - Conduit systems buried underground / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

Outside diameter according to DIN EN 61386-24

Bend radius applies to an ambient temperature of 20 °C. In case of lower temperatures, we recommend that the minimum bend radius be increased as follows: by a factor of > 1.5 x at approx. 10 °C, by a factor of > 2 x at approx. 0 °C).

All dimensions without tolerances are for information only.

FRÄNKISCHE Rohrwerke Gebr. Kirchner GmbH & Co. KG | Hellinger Str. 1 | 97486 Königsberg/Bayern
Tel. +49 9525 88-8123 | Fax +49 9525 88-2151 | info.elektro@fraenkische.de | www.fraenkische.com

Subject to change without notice.

Page 1 of 2

Last modified: 14.12.23

Kabuflex R plus 450 co2ntrol

N450

Material properties		
Zero halogen	EN 50642	•
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	
UV-resistant	DIN EN ISO 4892-1	
Highspeed		

Fields of application		
on plaster		machines
under plaster		hot asphalt
on wood		under screed
underground installation	•	prefabricated construction
in concrete		outdoor

Chemical properties	
Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
Limitedly resistant to	benzene, gaseous dry chlorine, nitric acid, terpentine
Not resistant to	-

Accessories		
Coupling	Kabuflex coupling transparent	192 50 ...
Coupling	Kabuflex coupling	199 10 ...
Sealing ring	Kabuflex profile sealing ring	199 80 ...
Wall lead through	Wall collar set	199 60 ...
End cap	Kabuflex SD end cap	199 70 ...
End cap	Kabuflex WD end cap	199 71 ...
Spacer	Spacer 2-fold	199 42 ...
Spacer	Spacer 4-fold	199 44 ...
Spacer	Spacer 6-fold	199 46 ...
Spacer	Spacer 8-fold	199 48 ...
Adaptor	Reducer	199 95 ...
Pressure sealing ring	Kabu-Seal	199 65 ...
internal seal	Kabu-IN	199 5 ...
internal seal	Kabu-IN DD	199 61 ...
end plug	Kabu-BV	199 50 ...

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-24 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

