



Wall collar set



Product description:

The wall collar is an ethylene propylene diene monomer (EPDM) wall lead through, in black, the set includes tightening straps and tightening locks.

This wall collar is used for completely tight wall lead throughs of Kabuflex conduits.



Special features

The wall collar is watertight up to 3.0 bar if installed correctly.

Cat. No.:	Type	Outside Ø mm	Content	PU	Weight PU/kg	Overall width mm	Core drilling mm	for conduits Ø mm
199 60 040	40	132	1	PCS	0,200	60,0	240	38-42
199 60 050	50	142	1	PCS	0,240	60,0	240	48-53
199 60 063	63	155	1	PCS	0,260	60,0	260	60-64
199 60 075	75	167	1	PCS	0,300	60,0	270	71-80
199 60 110	110	202	1	PCS	0,400	60,0	300	108-116
199 60 120	120/125	217	1	PCS	0,460	60,0	300	120-130
199 60 160	160	252	1	PCS	0,560	60,0	350	154-166
199 60 175	175	272	1	PCS	0,600	60,0	350	175-190

All dimensions without tolerances are for information only.



Wall collar set

Fields of application

on plaster		machines	
under plaster	•	hot asphalt	
on wood		under screed	•
underground installation		prefabricated construction	
in concrete	•	outdoor	

Chemical properties

Resistant to	acid emissions, beer, anti-freeze, fruit juices, methanol, fuels, hydraulic fluid and aromatic compounds
Limitedly resistant to	photographic developer, vinegar, milk, hydrochloric acid, weak acids and bases, amines and glycols over +70 °C
Not resistant to	concentrated sulfuric acid, chlorinated hydrocarbons, phenols

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

