



MMR-A outlet socket



Product description:

The multi-media conduit outlet socket is a polyolefin plastic wall outlet, available in white.

This outlet socket is used to insert and remove pre-assembled lines. An advantage is the possibility of retrofitting a plastered wall with an outlet socket.



Special features

The diameter of the core drilling bit for cutting the outlet hole for a retrofitted outlet socket is 60 mm.

Cat. No.:	Content	PU	Weight PU/kg	Overall width mm	Overall height mm
294 95 260	1	PCS	0,025	72,0	25,0

All dimensions without tolerances are for information only.



MMR-A outlet socket

Material properties		Fields of application	
Zero halogen	DIN VDE V 0604-2-100	• on plaster	• machines
Low smoke	DIN EN 61034-2	under plaster	hot asphalt
Non-flame propagating	DIN EN 61386-1	• on wood	under screed
UV-resistant	DIN 53387	underground installation	prefabricated construction
Highspeed		in concrete	outdoor

Chemical properties	
Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, beer, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
Limitedly resistant to	gasoline, benzene, nitric acid
Not resistant to	gaseous dry chlorine, terpentine

Risk analysis

The product has been manufactured and tested according to the harmonized standard 61386-1 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

