



MMR-B bend 90°



Product description:

The multi-media conduit bend 90° is a thermo-formed multi-media conduit. It is corrugated on the inside and the outside, and has an inside radius of approx. 90 mm. Available in grey.

This 90° bend is used to connect multi-media conduits at the corners using two multi-media coupling sleeves. Wall to suspended ceiling or wall to cavity floor. An advantage is the low-tension installation with a small installation radius.

Temperature resistance: -5° C to +90° C



Special features

Cat. No.:	Content	PU	Weight PU/kg	Overall width mm	Overall height mm	Overall length mm	Bend radius
294 60 292	1	PCS	0,101	92,0	190,0	190,0	90

All dimensions without tolerances are for information only.



MMR-B bend 90°

Material properties			Fields of application		
Zero halogen	DIN VDE V 0604-2-100	•	on plaster	•	machines
Low smoke	DIN EN 61034-2		under plaster	•	hot asphalt
Non-flame propagating	DIN EN 61386-1	•	on wood	•	under screed
UV-resistant	DIN 53387		underground installation		prefabricated construction
Highspeed			in concrete		outdoor

Chemical properties	
Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, beer, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
Limitedly resistant to	gasoline, benzene, nitric acid
Not resistant to	gaseous dry chlorine, terpentine

Risk analysis

The product has been manufactured and tested according to the harmonized standard 61386-1 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

