



## MMR-M coupling sleeve



### Product description:

The multi-media conduit coupling sleeve is a soft polyolefin coupling, available in black.

This coupling is used to connect multi-media conduits. An advantage is the tight and positive connection of multi-media conduits.



### Special features

Cat. No.:	Content	PU	Weight PU/kg	Overall width mm	Overall height mm	Overall length mm
294 51 292	1	PCS	0,041	99,0	55,0	60,0

All dimensions without tolerances are for information only.



## MMR-M coupling sleeve

Material properties		Fields of application	
<b>Zero halogen</b>	<b>DIN VDE V 0604-2-100</b>	• <b>on plaster</b>	• machines
Low smoke	DIN EN 61034-2	<b>under plaster</b>	• hot asphalt
<b>Non-flame propagating</b>	<b>DIN EN 61386-1</b>	• <b>on wood</b>	• under screed
UV-resistant	DIN 53387	underground installation	<b>prefabricated construction</b>
Highspeed		in concrete	outdoor

Chemical properties	
<b>Resistant to</b>	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, beer, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
<b>Limitedly resistant to</b>	benzene, gaseous dry chlorine, nitric acid, terpentine
<b>Not resistant to</b>	-

### Risk analysis

The product has been manufactured and tested according to the harmonized standard 61386-1 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

### Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

