



## MMR-S Multi-media conduit set



### Product description:

The multi-media conduit is an oval corrugated polyolefin conduit, available in grey.

Delivery includes:

1.5 m set: 1.5 m oval conduit, 2 outlet sockets, 2 end caps

2 x 1.5 m set: 2 x 1.5 m oval conduit, 2 outlet sockets, 2 end caps, 1 coupling

This multi-media conduit is used for concealed installations. The 1.5 m set for living rooms and the 2 x 1.5 m set for conference rooms, hospitals and schools. An advantage is the replaceability of cables with fitted plugs and the installation of a retrofitted multi-media outlet socket.



Temperature resistance: -5° C to +90° C



### Special features

The oval shape of the conduit allows installation depths of only 6 cm.

Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU	Weight PU/kg	Pallet content m	Bend radius > mm	Overall width mm	Overall height mm	Length m
294 10 092	92/50	82/40	92/50	1	PCS	0,486	270	300	92,0	50,0	1,5
294 11 092	92/50	82/40	92/50	2	PCS	0,972	270	300	92,0	50,0	3,0

All dimensions without tolerances are for information only.



## MMR-S Multi-media conduit set

Material properties		Fields of application	
Zero halogen	DIN VDE V 0604-2-100	<b>on plaster</b>	• machines
Low smoke	DIN EN 61034-2	<b>under plaster</b>	• hot asphalt
<b>Non-flame propagating</b>	<b>DIN EN 61386-1</b>	• <b>on wood</b>	• under screed
UV-resistant	DIN 53387	underground installation	<b>prefabricated construction</b>
Highspeed		in concrete	• outdoor

Chemical properties	
<b>Resistant to</b>	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, beer, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
<b>Limitedly resistant to</b>	gasoline, benzene, nitric acid
<b>Not resistant to</b>	gaseous dry chlorine, terpentine

### Risk analysis

The product has been manufactured and tested according to the harmonized standard 61386-1 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

### Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

