



Kabuflex profile sealing ring



Product description:

The WD profile sealing ring is a watertight sealing made of ethylene propylene diene monomer (EPDM), in black.

The WD profile sealing ring is used for each conduit in combination with the SD coupling to ensure a watertight connection of Kabuflex® S and Kabuflex® R.



Special features

The connection of Kabuflex with coupling and WD profile sealing ring is watertight up to 0.5 bar on each conduit.

Cat. No.:	Type	Content	PU	Weight PU/kg
199 80 040	40	1	PCS	0,001
199 80 050	50	1	PCS	0,002
199 80 063	63	1	PCS	0,003
199 80 075	75	1	PCS	0,010
199 80 090	90	1	PCS	0,010
199 80 110	110	1	PCS	0,020
199 80 120	120	1	PCS	0,020
199 80 125	125	1	PCS	0,020
199 80 145	145	1	PCS	0,040
199 80 160	160	1	PCS	0,050
199 80 175	175	1	PCS	0,040

All dimensions without tolerances are for information only.



Kabuflex profile sealing ring

Material properties		Fields of application	
Zero halogen	DIN VDE V 0604-2-100	on plaster	machines
Low smoke	DIN EN 61034-2	under plaster	hot asphalt
Non-flame propagating	DIN EN 61386-1	on wood	under screed
UV-resistant	DIN 53387	underground installation	• prefabricated construction
Highspeed		in concrete	outdoor

Chemical properties	
Resistant to	acid emissions, beer, anti-freeze, fruit juices, methanol
Limitedly resistant to	photographic developer, vinegar, milk, hydrochloric acid
Not resistant to	gasoline, diesel, fuel oil, paraffin, sulfuric acid

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123