



PV-COOR end cap

Product description:



The PV-COOR end cap is a PP-MOD-BS-UV end cap, in black, non-flame propagating.

This end cap is used for covering and sealing PV-COOR.



Temperature resistance range according to LV312-3:
-40° C to +135° C, short-term temperature resistance up to
+150° C
flammability: FMVSS 302 / UL 94 V2



Special features

UV-resistant for up to 10 years.

Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU
491 40 803	40x80	40x80	51,5x95,0	10	PCS

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in part

EN 61386-22:2011 Conduit systems for cable management - Part 22: Particular requirements - Pliable conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in part

All dimensions without tolerances are for information only.



PV-COOR end cap

Material properties		Fields of application		
Zero halogen	DIN VDE V 0604-2-100	on plaster	machines	•
Low smoke	DIN EN 61034-2	under plaster	hot asphalt	
Non-flame propagating	DIN EN 61386-1	• on wood	under screed	
UV-resistant	DIN 53387	• underground installation	prefabricated construction	
Highspeed		in concrete	outdoor	•

Chemical properties	
Resistant to	acids, bases, inorganic salts, fuels, mineral oils, greases and most common solvents
Limitedly resistant to	ether
Not resistant to	halogen-containing, oxidising and aromatic compounds

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-22 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

