



Reducer

Product description:



KG pipe adaptor made of PVC-U, in black.

This reducer is used as adaptor for joining Kabuflex® conduits to commercial KG pipes.



Special features

Profile sealing rings ensure a watertight connection up to 0.5 bar.

Cat. No.:	Type	Content	PU	Weight PU/kg	Overall length mm	Outside Ø mm KG-side
199 95 110	110	1	PCS	0,470	300,0	110
199 95 160	160	1	PCS	1,250	350,0	160

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-24:2011 Conduit systems for cable management - Part 24: Particular requirements - Conduit systems buried underground / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

All dimensions without tolerances are for information only.



Reducer

Fields of application

on plaster	machines	
under plaster	hot asphalt	
on wood	under screed	
underground installation	• prefabricated construction	
in concrete	outdoor	

Chemical properties

Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, nitric acid, hydrochloric acid, sulfuric acid, terpentine, detergent
Limitedly resistant to	gaseous dry chlorine
Not resistant to	benzene, beer

Accessories

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-24 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

