



ReMo UP socket



Product description:

The ReMo UP socket is an airtight flush-mounted socket, black RAL (9005).

The ReMo UP socket is used in particular for corrugated plastic conduits like FFKu-ReMo click and FFKuS DATALIGHT®. An advantage is that it allows for rear insertion. This allows for inserting the conduit from the outside wall directly to the socket.



Cat. No.:	Type	Content	PU	Overall width mm	Overall length mm
266 80 025	25	25	PCS	63,0	66,0

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-22:2011 Conduit systems for cable management - Part 22: Particular requirements - Pliable conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

All dimensions without tolerances are for information only.



ReMo UP socket

Material properties		Fields of application	
Zero halogen	DIN VDE V 0604-2-100	on plaster	machines
Low smoke	DIN EN 61034-2	under plaster	• hot asphalt
Non-flame propagating	DIN EN 61386-1	• on wood	under screed
UV-resistant	DIN 53387	underground installation	prefabricated construction
Highspeed		in concrete	outdoor

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-22 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

