



SN-E-V



Product description:

SN-E-V is a galvanised threaded nipple made of rolled mild steel with zinc-nickel alloy plating.

This threaded nipple is used for SM-E-V threaded couplings and galvanised SGR-E-V steel lock rings.



VDE 0605
DIN EN 61386-21



Special features

This product is suited for the installation of circuit integrity cables (E30/ E60/ E90) and has been tested in the system.

Cat. No.:	Type	Outside Ø mm	Content	PU	Weight PU/kg	Overall length mm	Thread
204 70 016	16	15,8	25	PCS	0,225	30,0	M16x1,5
204 70 020	20	19,8	50	PCS	0,650	30,0	M20x1,5
204 70 025	25	24,7	50	PCS	1,050	36,0	M25x1,5
204 70 032	32	31,7	50	PCS	1,700	44,0	M32x1,5
204 70 040	40	39,7	25	PCS	1,275	50,0	M40x1,5
204 70 050	50	49,7	10	PCS	0,750	55,0	M50x1,5
204 70 063	63	62,7	5	PCS	0,695	60,0	M63x1,5

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-21:2011 Conduit systems for cable management - Part 21: Particular requirements - Rigid conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

All dimensions without tolerances are for information only.



SN-E-V

Material properties			Fields of application		
Zero halogen	DIN VDE V 0604-2-100		on plaster	• machines	•
Low smoke	DIN EN 61034-2		under plaster	• hot asphalt	•
Non-flame propagating	DIN EN 61386-1	•	on wood	• under screed	•
UV-resistant	DIN 53387		underground installation	• prefabricated construction	•
Highspeed			in concrete	• outdoor	•

Chemical properties	
Resistant to	oils, paint, water, weak alkalis and solvents
Limitedly resistant to	acids and strong bases
Not resistant to	sulphur

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-21 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

