

## Road and track drainage Shaft systems

### StrabuControl® 600 V HP Piggyback flushing and inspection shaft

**PE-HD flushing and inspection shaft in piggyback arrangement, consisting of AquaPipe transport pipe and top Strabusil or StormPipe DN 150 drainage pipe; with freely selectable connection angle between 90° and 270°; inside diameter of base body greater than 600 mm; colour: black**



#### Technical data

Application:	Flushing and inspection shaft in piggyback arrangement for Strabusil and/or StormPipe drainage pipes and AquaPipe transport pipes for all fields of civil engineering and road engineering.
Material / raw material:	PE-HD (polyethylene)
Specification:	Design as shaft with piggyback arrangement, with freely selectable connection angle between 90° and 270°
Nominal connection diameters (DN):	200 – 350
Effective height: [m]	1.00
Total height: [m]	1.06
Inside diameter of base body: [m]	> 0.60
Clear pipe spacing between transport pipe and drainage pipe: [m]	0.15
Weight: [kg]	< 21
Technical characteristics:	Monolithic base body; UV-resistant; resistant to acids, bases, oils, greases and cement according to DIN 8075; extremely durable and hard-wearing; high impact strength; extension pipe can be cut to length; with integrated compensating area; watertight connection of pipes according to DIN 4262-1 possible; installation in traffic areas possible; connection of commercially available standard shaft covers 625 mm possible
Miscellaneous:	Project shafts according to order form For accessories, see price catalogue and product documentation "Shaft systems for road drainage"



[www.fraenkische.com](http://www.fraenkische.com)