



VES-E

**Product description:**

VES-E is a stainless steel push-fit end cap, made of 1.4571 material, AISI 316 TI.

This push-fit end cap is used for joining V2 Steck-ES and V4 Steck-ES stainless steel conduits. An advantage is that edge protection is provided.



VDE 0605
DIN EN 61386-21



Cat. No.:	Type	Outside Ø mm	Content	PU	Weight PU/kg	Overall length mm
208 90 016	16	23,3	5	PCS	0,100	55,0
208 90 020	20	28,2	5	PCS	0,145	55,0
208 90 025	25	35,3	5	PCS	0,030	60,0
208 90 032	32	44,0	5	PCS	0,290	70,0
208 90 040	40	54,0	3	PCS	0,372	80,0
208 90 050	50	66,5	3	PCS	0,366	95,0
208 90 063	63	82,5	3	PCS	0,366	110,0

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-21:2011 Conduit systems for cable management - Part 21: Particular requirements - Rigid conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

All dimensions without tolerances are for information only.



VES-E

Material properties		Fields of application	
Zero halogen	DIN VDE V 0604-2-100	on plaster	• machines
Low smoke	DIN EN 61034-2	under plaster	• hot asphalt
Non-flame propagating	DIN EN 61386-1	• on wood	• under screed
UV-resistant	DIN 53387	underground installation	• prefabricated construction
Highspeed		in concrete	• outdoor

Chemical properties	
Resistant to	ammonia, gasoline, vinegar, methanol, mineral oil
Limitedly resistant to	acid emissions, sea water, hydrochloric acid
Not resistant to	chlorine, nitric acid, sulfuric acid

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-21 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

