



Fibre net EZA-t

Product description:



Fibre net EZA-t is a halogen-free and flame resistant two-piece and high tensile strength single strand sealing available in white.

This single strand sealing is used to seal occupied and unused FFKu-Fibre net. Temperature range: 0–50 °C.



Special features

Pressure: gastight and watertight 0.5 bar

Strength of the connection clamp: min. 650 N

Cat. No.:	Type	Content	PU	Weight PU/kg	Overall length mm	Outside Ø mm with tabs	for conduits Ø mm	For cable Ø mm
265 72 007	7	25	PCS	0,275	43,0	21,0	7	0,8 - 2,5
265 72 410	10	25	PCS	0,375	43,0	27,0	10	1,8 - 3,5
265 72 507	7	25	PCS	0,275	43,0	21,0	7	2,0 - 4,0
265 72 610	10	25	PCS	0,375	43,0	27,0	10	3,0 - 5,0
265 72 612	12	25	PCS	0,425	43,0	28,0	12	3,0 - 5,0
265 72 614	14	25	PCS	0,500	43,0	30,0	14,0	3,0 - 5,0
265 72 710	10	25	PCS	0,375	43,0	27,0	10,0	5,0 - 6,5
265 72 712	12	25	PCS	0,425	43,0	28,0	12,0	5,0 - 6,5
265 72 714	14	25	PCS	0,500	43,0	30,0	14,0	5,0 - 6,5
265 72 814	14	25	PCS	0,500	43,0	30,0	14,0	6,5 - 8,0

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in part

EN 61386-22:2011 Conduit systems for cable management - Part 22: Particular requirements - Pliable conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in part

All dimensions without tolerances are for information only.



Fibre net EZA-t

Material properties		
Zero halogen	EN 50642	
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	•
UV-resistant	DIN EN ISO 4892	
Highspeed		

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-22 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123